



Codice SKU: **NETTPL318**

Prezzo: 36,00 € (IVA inclusa)

TP-LINK ARCHER AX1800 T20E WIFI 574Mbps+ 1210Mbps Bluetooth 5.2

Descrizione

CARATTERISTICHE HARDWARE

Dimensions: 120.8 × 78.5 × 20.9 mm

Tipo di antenna: 2x High-Gain Dual Band Antennas

Chipset: Realtek Wi-Fi 6 Chipset

CARATTERISTICHE WIRELESS

Standard wireless:

- IEEE 802.11ax/ac/n/a 5 GHz
- IEEE 802.11ax/n/g/b 2.4 GHz
- Bluetooth 5.2

WLAN Signal Rate (5 GHz):

- 11ax: Up to 1201 Mbps(dynamic)
- 11ac: Up to 867 Mbps(dynamic)
- 11n: Up to 300 Mbps(dynamic)
- 11a: Up to 54 Mbps(dynamic)

WLAN Signal Rate (2.4 GHz):

- 11ax: Up to 574 Mbps(dynamic)
- 11n: Up to 300 Mbps(dynamic)
- 11g: Up to 54 Mbps(dynamic)
- 11b: Up to 11 Mbps(dynamic)

WLAN Reception Sensitivity (5 GHz):

- 11ax HE80: -57.0dBm
- 11ax HE40: -60.0dBm
- 11ax HE20: -63.0dBm
- 11ac VHT80: -59.5dBm
- 11ac VHT40: -62.5dBm

- 11ac VHT20: -67.5dBm
- 11n HT40: -69.5dBm
- 11n HT20: -72.5dBm
- 11a 54Mbps: -74.0dBm
- 11a 6Mbps: -94.5dBm

WLAN Reception Sensitivity (2.4GHz):

- 11ax HE40: -60.0dBm
- 11ax HE20: -63.0dBm
- 11n HT40: -69.5dBm
- 11n HT20: -72.5dBm
- 11g 54Mbps: -74.0dBm
- 11b 11Mbps: -88.0dBm

WLAN Transmit Power:

- 5 GHz : 27dBm(FCC) / 23dBm(CE) (EIRP)
- 2.4 GHz : 25dBm(FCC) / 20dBm(CE) (EIRP)

WLAN Modes: Infrastructure mode

Sicurezza wireless: Support 64/128 bit WEP, WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x

Modulazione: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM, 1024QAM

ALTRO

Certificazione: CE, FCC, RoHS

Contenuto della confezione:

- Archer TX20E
- Two High-Gain Dual Band Antennas
- Low-Profile Bracket
- Bluetooth Header Cable
- Quick Installation Guide
- Resource CD

Requisiti di sistema: Windows 11/10(64-bit) only

Ambiente:

- Operating Temperature: 0â„ƒ~40â„ƒ (32â„°~104â„°)
- Storage Temperature: -40â„ƒ~70â„ƒ (-40â„°~158â„°)
- Operating Humidity: 10%~90% non-condensing
- Storage Humidity: 5%~90% non-condensing